


JU206/JU308
外形尺寸 · DIMENSIONS(mm)


	A	D	B	E	C
JU206 (φ 2X6)	6.2	6.0	φ 2.1	φ 0.2	0.7
JU308 (φ 3X8)	8.3	10.0	φ 3.1	φ 0.3	0.8

技术参数 · PARAMETERS

参数	ITEM	JU308(φ 3X8)	JU206(φ 2X6)
频率范围	Frequency Range (KHz)	32.768KHz/40.0KHz/75.0KHz/76.8KHz	32.768KHz/40.0KHz/75.0KHz/76.8KHz
调整频差	Frequency Tolerance	10ppm/±50ppm 20ppm±100ppm	
负载电容	Load Capacitance	12.5pF(Typ.)	
测试激励功率	Measurement Drive Level	1.0±0.2 μ w	
谐振电阻	Series Resistance	30k Ω max	40k Ω max
Q值	Q-Factor	80,000(Typ.) 50,000min	70,000(Typ.) 40,000min
拐点温度	Turnover Temperature	25°C ± 3°C	25°C ± 3°C
二次温度曲线系数	Parabolic Curvature Constant	-0.036 ± 0.006ppm/°C	
静态电容	Shunt Capacitance	1.3pF (Typ.) 2.0pFmax.	1.1pF(Typ.) 1.8pFmax.
容量比	Capacitance Ratio	530 (Typ.) 650max.	470(Typ.) 650max.
工作温度	Operating Temp Range	-10°C ~ +60°C	
储存温度	Storage Temp Range	-20°C ~ +70°C	
耐冲击性	Shock Resistance	Natural drop 3 Times on Hard Wooden Board from height of 30cm	
绝缘电阻	Insulation Resistance	500M Ω min./DC100V	

FREQUENCY VS CL
FREQUENCY VS TEMPERATURE
